



# Accessories

## Model DC7200A, DC7200 Dual Directional Coupler

### Features:

- 1 - 6 GHz
- 250 W CW, 1 - 6 GHz
- Excellent frequency range and power handling
- Forward and Reflected power monitoring

### Applications:

- Use with S-Series models within frequency and power range

To view our full accessories portfolio visit:  
<https://arworld.us/test-accessories>

Amplifier Research Corporation  
160 Schoolhouse Rd  
Souderton, PA 18964  
215.723.8181  
info@arworld.us  
www.arworld.us  
ISO 9001:2015 Certified  
ISO 17025 :2017 Accredited

The Models DC7200A & DC7200 are dual directional couplers with excellent frequency range and power handling capability. The wide range assures flexibility in coupling medium power amplifiers to oscilloscopes, voltmeters, power meters, spectrum analyzers and other measuring instruments. The dual directional design allows the user to monitor both forward and reflected power, a much-needed characteristic in RF susceptibility testing for amplifier overdrive protection, field control and load protection. Low insertion loss allows efficient coupling to the load.

The Model DC7200A/DC7200 series is uniquely suited for use with our line of 1- 6 GHz S-Series power amplifiers or other amplifiers operating within this frequency and power range.

The export classification for this equipment is EAR99. These commodities, technology or software are controlled for export in accordance with the U.S. Export Administration Regulations. Diversion contrary to U.S. law is prohibited.

- 1 – 6 GHz
- 250 W CW

Specifications				
Parameter	Minimum	Typical	Maximum	Unit
Power (CW, maximum), 1 – 6 GHz			250	W
Operating Frequency	1		6	GHz
Coupling Factor (nominal)		40 ± 1.2		dB
Coupling Flatness		±0.8		dB
Directivity	15	18		dB
Insertion Loss			0.2	dB
Impedance		50		Ohm
with Type N input connector		1.2:1		VSWR
Export classification	EAR99			

Mechanical Specifications		
Parameters		Unit
Size (W x H x D)	6.8 x 5.1 x 3.05	cm
	2.7 x 2.0 x 1.2	in
Weight	0.27	kg
	0.6	lb

Connector interfaces				
	DC7200A	DC7200AM1	DC7200	DC7200M1
Function	Type	Type		
Mainline J1/J2	N (M) / N (F)	N (M) / N (F)	N (F) / N (F)	N (F) / N (F)
Coupled J3/J4	N (F) / N (F)	SMA (F) / SMA (F)	N (F) / N (F)	SMA (F) / SMA (F)

Amplifier Research recommends the use of low-pass filters (for example, Mini-Circuits VLF-6400+ or equivalent AR P/N 10045273 filter and AR P/N 10035328 adapter) on the coupled ports of this coupler. This practice ensures that in-band coupled power is not overstated due to exaggerated contributions from out-of-band harmonic content.