



**DC7210A,
DC7210**
Dual Directional
Coupler

- 0.7GHz–6GHz

Features

The Models DC7210A & DC7210 are dual directional couplers with excellent frequency range and power handling capability. The wide range assures flexibility in coupling medium power amplifiers to oscilloscopes, voltmeters, power meters, spectrum analyzers and other measuring instruments. The dual directional design allows the user to monitor both forward and reflected power, a much needed characteristic in RF susceptibility testing for amplifier overdrive protection, field control and load protection. Low insertion loss allows efficient coupling to the load.

The Model DC7210A/DC7210 series is uniquely suited for use with our 0.7-6 GHz, 350S1G6A power amplifier or other amplifiers operating within this frequency and power range.

The export classification for this equipment is EAR99. These commodities, technology or software are controlled for export in accordance with the U.S. Export Administration Regulations. Diversion contrary to U.S. law is prohibited.

Specifications

- | | |
|--|---|
| FREQUENCY RANGE: 0.7–6GHz | CONNECTORS: See Model Configurations |
| POWER (Maximum Watts): 500W CW | WEIGHT: 0.27 kg (0.6 lb) |
| COUPLING FACTOR: See Model Configurations | SIZE (WxHxD): 54.6 x 50.8 x 34.5 mm (2.15 x 2.0 x 1.36 in) |
| FLATNESS: ± 1.0dB | EXPORT CLASSIFICATION: EAR99 |
| DIRECTIVITY (Minimum): 15 dB | |
| INSERTION LOSS: 0.2 dB maximum | |
| IMPEDANCE (Main Line): 50 ohms, VSWR 1.35:1 maximum | |

Model Configurations			
Model Number	Main Line J1/J2	Coupler Connectors J3/J4	Coupling Factor (Includes flatness)
DC7210A	7-16(M)/7-16(F)	N(F)/N(F)	50dB ± 1.2dB
DC7210AM1	7-16(M)/7-16(F)	N(F)/N(F)	60dB ± 1.2dB
DC7210	7-16(F)/7-16(F)	N(F)/N(F)	50dB ± 1.2dB

AR RF/Microwave
Instrumentation
160 School House Rd
Souderton, PA 18964
215-723-8181

For an applications engineer call: 800.933.8181

www.arworld.us

To order AR Products, call 215.723.8181. For an applications engineer call: 800.933.8181. Direct to Service call: 215.723.0275 or email: service@arworld.us For Faxing Orders: 866.859.0582 (Orders Only Please) info@arworld.us

Approved for public release by AR RF/Microwave Instrumentation

041619

